

PRODUCT CONFIGURATOR

	13					
PRODUCT						
SERIES 1300						
POWER						
A Universal AC (90-264 VAC)						
B 18-36 VDC (24 VDC nominal)						
C 12 VDC						
SENSOR CONFIGURATION ⁽¹⁾						
1 Local O ₂ sensor only						
2 Remote O ₂ sensor only (no local)						
3 Two remote O ₂ sensors (no local)						
4 One local and one remote O ₂ sensor						
5 One local and two remote O ₂ sensors						
BATTERY BACKUP						
U Battery Backup						
X (none)						
HORN & STROBE ANNUNCIATOR(S) ⁽²⁾						
Quantity of 1-8						
X (none)						
SERIAL COMMUNICATIONS						
R RS-232 ⁽³⁾						
S RS-485						

(1) All remote sensors come with 10 feet of cable. Additional cable up to a maximum of 1,000 feet is available.

(2) Each Horn & Strobe comes with 10 feet of cable. Additional cable is available. Note: The maximum length of cable for 4 horn and strobes is 500 feet total. Consult factory for applications requiring more than 4 horn and strobes.

(3) The Series 1300 Oxygen Deficiency Monitor comes equipped with RS-232 serial communications standard. When the optional RS-485 is ordered, it replaces RS-232.

Examples:

1. Series 1300 with AC power and a local sensor (P/N 13A1XXR)
2. Series 1300 with 12 VDC power, 2 remote sensors, and RS-485 (P/N 13C3XXS)
3. Series 1300 with 18-36 VDC power, 1 local and 2 remote sensors, four horn & strobes, and RS-485 (P/N 13B5X4S)