

Ordering Information

Series 3500 Trace O₂ Transmitter

Measuring Ranges (select one)

(A) 0-10 ppm, (B) 0-50 ppm, (C) 0-100 ppm, (D) 0-500 ppm,
(E) 0-1,000 ppm, (F) 0-5,000 ppm, (G) 0-10,000 ppm. (H) 0-20,000

Optional Sample Filter (select one)

(X) No filter.
(F) High capacity filter (395S).

Optional Pressure Regulator (select one).

(X) No regulator.
(R) 100 psig (7.03kg/cm²) capacity (3LPR).

Optional Flowmeter (select one).

(X) No flowmeter.
(M) With flowmeter (3FLM).

Optional NEMA 7 Enclosure (select one).

(X) Standard Enclosure.
(7) NEMA 7 Enclosure.

Optional CO₂ Resistant Sensor (select one)

(X) Standard Sensor.
(CO₂) CO₂ Resistant Sensor.

P/N 3500 - X - X - X - X - X - X

Configuration Example : Series 3500 Trace O₂ Transmitter with a range of 0-10,000 PPM, optional flowmeter, and optional CO₂ Resistant Sensor. (p/n 3500-G-X-X-M-X-CO₂)

Note:

1. The standard Series 3500 Trace Oxygen Transmitter is housed in a NEMA 4 (watertight) housing. If equipped with the optional NEMA 7 enclosure, the instrument can be used in areas requiring Class 1, Groups B, C, D, Div 1; or Class II, Groups E,F,G; or Class III equipment.