

Ordering Information

Series 3520 Portable Trace Oxygen Analyzer to include
NICAD batteries and AC¹ battery charger.

Measuring Ranges in Parts Per Million² (select one)

(B) 0-50 (C) 0-100 (D) 0-500 (E) 0-1,000
(F) 0-5,000 (G) 0-10,000 (H) 0-20,000

Sample Connections (select one)

(1) 1/4" Stainless Steel compression fittings.

Optional Pressure Regulator (select one)

(X) No regulator
(R) Regulator with aluminum housing with a maximum input pressure
100 psig (7.03kg/cm²) (3LPR).

Optional Flowmeter (select one)

(X) No flowmeter
(M) With flowmeter (3FLM).

Optional Sample Pump

(X) No sample pump.
(P) On-Board DC pump (3PMPD).
(Installed on rear of analyzer)

Optional Sample Filter

(X) No filter.
(F) High capacity Filter with SS Body and SS Sintered
Filter (395S).

Optional CO₂ Resistant Sensor (select one)

(X) Standard Sensor.
(CO₂) CO₂ Resistant Sensor.

P/N 3520 - X - X - X - X - X - X - X

Configuration example :Series 3520 Trace Oxygen Analyzer with a range of 0-1,000 PPM, 1/4" Stainless Steel
compression fittings, optional flowmeter, and optional sample pump. (p/n 3520-E-1-X-M-P-X-X)

¹ At the time of order placement, specify the AC voltage required for the battery charger.

² Replacement Sensor part number 3SEN