

PRODUCT CONFIGURATOR

| | 13 | | | X | | R |
|---|----|--|--|---|--|---|
| PRODUCT SERIES 1300 | | | | | | |
| POWER A Universal AC (90-264 VAC) B 18-36 VDC (24 VDC nominal) C 12 VDC | | | | | | |
| SENSOR CONFIGURATION ⁽¹⁾ 1 Local O ₂ sensor only 2 Remote O ₂ sensor only (no local) 3 Two remote O ₂ sensors (no local) 4 One local and one remote O ₂ sensor 5 One local and two remote O ₂ sensors | | | | | | |
| X (none) | | | | | | |
| HORN & STROBE ANNUNCIATOR(S) ⁽²⁾ Quantity of 1-8 X (none) | | | | | | |
| SERIAL COMMUNICATIONS R RS-232 ⁽³⁾ | | | | | | |

(1) All remote sensors come with 10 feet of cable. Additional cable up to a maximum of 1,000 feet is available.

(2) Each Horn & Strobe comes with 10 feet of cable. Additional cable is available. Note: The maximum length of cable for 4 horn and strobes is 500 feet total. Consult factory for applications requiring more than 4 horn and strobes.

(3) The Series 1300 Oxygen Deficiency Monitor comes equipped with RS-232 serial communications standard.

Examples:

1. Series 1300 with AC power and a local sensor (P/N 13A1XXR)
2. Series 1300 with 12 VDC power, 2 remote sensors (P/N 13C3XXR)
3. Series 1300 with 18-36 VDC power, 1 local and 2 remote sensors, four horn & strobes (P/N 13B5X4R)